



Pos. Quantity Description

**1 Disinfection, cleaning and drying cabin
DRTK-H2 for 12 helmets**

Fully automatic disinfection, cleaning and drying cabin for the simultaneous care of up to 12 helmets.

Thanks to the recirculation process and the use of environmentally friendly cleaning agents and disinfectants, these systems are very environmentally friendly.

The helmets pass through a water curtain for cleaning and disinfection.

During drying, air is blown directly onto and into the helmets.

With the following technical data:

Cabin:

- Aluminium profile housing for better sound insulation and thermal insulation for optimal energy utilisation
Powder-coated on both sides, resulting in almost no maintenance required
- Stainless steel drip tray
- Cover grille over the heating elements in stainless steel design
- Water extraction from below, resulting in no residual water in the tray area
- Single-pane safety glass door
- Contactless door contact switch
- 4 heavy-duty castors

Width: approx. 1465 mm
Depth: approx. 825 mm
Height: approx. 1970 mm
Weight: approx. 200 kg



Washing:

- Rotating wheel with mounting adapter for 12 helmets
- Powerful self-priming pump
- Tested standard washing programme
A pre-wash with clean water, a disinfectant cleaning wash and 4 x rinses with clean water

Drying:

- High-performance fan with thermal protection
- 2.1 kW heating coil with triple protection against overheating

Disinfection:

- Automatic dosing device with low-maintenance hose pump and suction lance
- 2.5 kW hot water preparation to ensure disinfection and cleaning performance.

Controls and displays:

- Siemens touch panel
- Siemens control system for quick commissioning with integrated basic settings and standard programmes
- The control panel features the following functions:
 - Touch panel with visual menu navigation
 - Emergency stop mushroom button
 - On/off switch
 - Complete cycle including drying approx. 2.5 hours



Safety features:

- Level control with integrated overflow protection
- Automatic shutdown in case of malfunction
- Low voltage 24V
- Safety thermostats for water and air

Connections:

Water connection: $\frac{3}{4}$ external thread
Waste water connection: $\frac{3}{4}$ external thread
Exhaust air connection: 125 mm diameter
Electrical connection: 230V 50Hz

Our products are subject to continuous development. We reserve the right to change the design, execution and materials at short notice and without prior notice.
As of 2025

3/3

AXEL ROTHER
Engineering
Gartenweg 11
74743 Seckach

Telefon - Nr.: 06293/928 7300
UST.ID.: DE263476717
Homepage: www.al-ro.de
E-Mail: info@al-ro.de

Bankverbindung:
IBAN
BIC:

Raiffeisenbank EG Elztal
DE50660691030025026438
GENODE61ELZ