



Pos. Quantity Description

- 1** Disinfection, cleaning and drying cabinet
DRTK-HM4 Combi for 4 helmets, 8 masks,
8 lung regulators

Fully automatic disinfection, cleaning and drying cabinet for
the simultaneous care of up to
4 helmets, 8 masks or 8 lung regulators.

These systems are very environmentally friendly thanks to
the recirculation process used and the use of
environmentally friendly cleaning agents and disinfectants.
The helmets pass through a water curtain for cleaning and
disinfection.

During drying, air is blown directly onto or into the helmets.

With the following technical data:

Cabin:

- Aluminium profile housing for better
sound insulation and thermal insulation for
optimal energy utilisation
Powder-coated on both sides, resulting in almost no
maintenance required
- Stainless steel drip tray
- Cover grille over the heating elements in stainless steel
design
- Water extraction from below, resulting in
no residual water in the tray area
- Single-pane safety glass door
- Contactless door contact switch
- 4 adjustable feet

Width: approx. 1165 mm
Depth: approx. 800 mm
Height: approx. 1895 mm
Weight: approx. 180 kg



Washing:

- Rotating wheel with mounting adapter for 4 helmets, 8 masks and 8 lung regulators
- Powerful self-priming pump
- Tested standard washing programme
A pre-wash with clean water, a disinfectant cleaning wash and 4 x rinses with clean water

Drying:

- High-performance fan with thermal protection
- 1.8 kW heating coil with triple protection against overheating

Disinfection:

- Automatic dosing device with low-maintenance peristaltic pump and suction lance
- 2.5 kW hot water preparation to ensure disinfection and cleaning performance.

Controls and displays:

- Siemens touch panel
- Siemens control system
for quick commissioning with integrated basic settings and standard programmes
- The control panel features the following functions:
 - Touch panel with visual menu navigation
 - Emergency stop button
 - On/off switch



Safety features:

- Level control with integrated overflow protection
- Automatic shut-off in case of malfunction
- Low voltage 24V
- Safety thermostats for water and air

Connections:

Water connection: $\frac{3}{4}$ external thread

Waste water connection: $\frac{3}{4}$ external thread

Exhaust air connection: 125 mm diameter

Electrical connection: 230V 50Hz

Our products are subject to continuous development. We reserve the right to change the design, execution and materials at short notice and without prior notice.
As of 2025

3/3

AXEL ROTHER
Engineering
Gartenweg 11
74743 Seckach

Telefon - Nr.: 06292/929 202
UST.ID.: DE263476717
Homepage: www.al-ro.de
E-Mail: info@al-ro.de

Bankverbindung:
IBAN
BIC:

Raiffeisenbank EG Elztal
DE50660691030025026438
GENODE61ELZ