



Washing:

- Rotating wheel with mounting adapter for 24 masks
- Powerful self-priming pump
- Tested standard washing programme
A pre-wash with clean water, a
disinfectant cleaning wash and
4 x rinses with clean water

Drying:

- High-performance fan with thermal protection
- 1.8 kW heating coil with triple protection
against overheating

Disinfection:

- Automatic dosing device with
low-maintenance peristaltic pump and suction lance
- 2.5 kW hot water preparation to ensure
disinfection and cleaning performance.

Controls and displays:

- Siemens touch panel
- Siemens control system
for quick commissioning with integrated basic
settings and standard programmes
- The control panel features the following
functions:
 - Touch panel with visual menu navigation
 - Emergency stop mushroom button
 - On/off switch
- **Complete cycle including drying approx. 120 min.**



Safety features:

- Level control with integrated overflow protection
- Automatic shutdown in case of malfunction
- Low voltage 24V
- Safety thermostats for water and air

Connections:

Water connection: $\frac{3}{4}$ external thread

Waste water connection: $\frac{3}{4}$ external thread

Exhaust air connection: 125 mm diameter

Electrical connection: 230V 50Hz

Our products are subject to continuous development. We reserve the right to change the design, execution and materials at short notice and without prior notice.
As of 2025