



Pos. Quantity Description

**1 DRTK-M3 disinfection, cleaning and drying cabinet for
24 breathing masks**

Fully automatic disinfection, cleaning and drying cabinet for the simultaneous care of up to 24 breathing masks and/or 12 lung regulators

These systems are very environmentally friendly thanks to the recirculation process used and the use of environmentally friendly cleaning agents and disinfectants. The helmets pass through a water curtain for cleaning and disinfection.

During drying, air is blown directly onto or into the helmets

with the following technical data:

Cabin:

- Aluminium profile housing for better sound insulation and thermal insulation for optimal energy utilisation
Powder-coated on both sides, resulting in almost no maintenance required
- Stainless steel drip tray
- Cover grille over the heating elements in stainless steel design
- Water extraction from below, resulting in no residual water in the tray area
- Single-pane safety glass door
- Contactless door contact switch
- 4 adjustable feet

Width: approx. 1165 mm
Depth: approx. 800 mm
Height: approx. 1895 mm
Weight: approx. 180 kg



Washing:

- Rotating wheel with mounting adapter for 24 masks and/or 12 lung regulators
- Powerful self-priming pump
- Tested standard washing programme
A pre-wash with clean water, a disinfectant cleaning wash and 4 x rinses with clean water

Drying:

- High-performance fan with thermal protection
- 1.8 KW heating coil with triple protection against overheating

Disinfection:

- Automatic dosing device with low-maintenance peristaltic pump and suction lance
- 2.5 KW hot water preparation to ensure disinfection and cleaning performance.

Controls and displays:

- Siemens touch panel
- Siemens control system
for quick commissioning with integrated basic settings and standard programmes
- The control panel features the following functions:
 - Touch panel with visual menu navigation
 - Emergency stop mushroom button
 - On/off switch
- **Complete cycle including drying approx. 120 min.**



Safety features:

- Level control with integrated overflow protection
- Automatic shutdown in case of malfunction
- Low voltage 24V
- Safety thermostats for water and air

Connections:

Water connection: $\frac{3}{4}$ external thread
Waste water connection: $\frac{3}{4}$ external thread
Exhaust air connection: 125 mm diameter
Electrical connection: 230V 50Hz

Our products are subject to continuous development. We reserve the right to change the design, construction and materials at short notice and without prior notice.
As of 2025